



应用

- 适用于电器、仪表和电子设备及自动化装置用连线。

结构

- 多股退火裸铜丝或镀锡铜丝绞合
- PVC 绝缘
- 镀锡或裸软铜线编织屏蔽
- PVC 护套

特点

- 可通过 GB18380.1 垂直耐燃试验
- 使用标准厚度、易剥、易裁
- 具有抗酸碱、防霉、耐油、防潮、环保等特性

性能

- 额定温度：70℃
- 额定电压：300/300V

编号	芯数 × 截面 mm ²	绝缘厚度 mm	护套厚度 mm	平均外径		70℃时绝缘电阻最小值 MΩ.km
				下限 mm	上限 mm	
1005RVVP0020005	2 × 0.5	0.6	0.9	7.7	9.6	49.05
1005RVVP00200075	2 × 0.75	0.6	0.9	8.0	10.0	57.68
1005RVVP0020001	2 × 1.0	0.6	0.9	8.2	10.3	71.22
1005RVVP0020015	2 × 1.5	0.7	1.0	9.3	11.6	92.90
1005RVVP0020025	2 × 2.5	0.8	1.1	10.7	13.3	143.53
1005RVVP0030005	3 × 0.5	0.6	0.9	8.0	10.0	58.20
1005RVVP00300075	3 × 0.75	0.6	0.9	8.3	10.4	69.62
1005RVVP0030001	3 × 1.0	0.6	1.0	8.8	11.0	93.67
1005RVVP0030015	3 × 1.5	0.7	1.0	9.7	12.1	122.92
1005RVVP0030025	3 × 2.5	0.8	1.1	11.3	14.0	74.75
1005RVVP0040005	4 × 0.5	0.6	0.9	8.5	10.7	74.75
1005RVVP00400075	4 × 0.75	0.6	1.0	9.1	11.3	86.95
1005RVVP0040001	4 × 1.0	0.6	1.0	9.4	11.7	113.06
1005RVVP0040015	4 × 1.5	0.7	1.1	10.7	13.2	157.24
1005RVVP0040025	4 × 2.5	0.8	1.2	12.6	15.5	231.10
1005RVVP0050005	5 × 0.5	0.6	1.0	9.3	11.6	86.71
1005RVVP00500075	5 × 0.75	0.6	1.0	9.7	12.1	104.44
1005RVVP0050001	5 × 1.0	0.6	1.1	10.3	12.8	150.57
1005RVVP0050015	5 × 1.5	0.7	1.2	11.8	14.7	183.97
1005RVVP0050025	5 × 2.5	0.8	1.3	13.9	17.2	272.80
1005RVVP0050005	6 × 0.5	0.6	1.0	9.9	12.4	99.40
1005RVVP00500075	6 × 0.75	0.6	1.1	10.5	13.1	120.59
1005RVVP0050001	6 × 1.0	0.6	1.1	11.0	13.6	171.85
1005RVVP0050015	6 × 1.5	0.7	1.2	12.7	15.7	211.08
1005RVVP0050025	6 × 2.5	0.8	1.4	15.2	18.7	315.00