

# ANYCERT-CCC-RVV

## RVV 多芯软导体聚氯乙烯绝缘护套电缆



### 应用

- 适用于一般电子、电器设备电源连线。

### 结构

- 单根或多股退火裸铜丝或镀锡铜丝绞合
- PVC 绝缘
- PVC 护套

### 特点

- 可通过 GB18380.1 垂直耐燃试验
- 使用标准厚度、易剥、易裁
- 具有抗酸碱、防霉、耐油、防潮、环保等特性

### 性能

- 额定电压：300/500V
- 额定温度：70℃

| 编号              | 芯数 × 截面<br>mm <sup>2</sup> | 绝缘厚度<br>mm | 护套厚度<br>mm | 平均外径  |       | 70℃时绝缘电阻最小值<br>MΩ.km |
|-----------------|----------------------------|------------|------------|-------|-------|----------------------|
|                 |                            |            |            | 下限 mm | 上限 mm |                      |
| 1005RVV0020005  | 2 × 0.5                    | 0.6        | 0.7        | 5.2   | 6.6   | 0.012                |
| 1005RVV00200075 | 2 × 0.75                   | 0.6        | 0.8        | 5.7   | 7.2   | 0.012                |
| 1005RVV002001   | 2 × 1.0                    | 0.6        | 0.8        | 5.9   | 7.5   | 0.010                |
| 1005RVV0020015  | 2 × 1.5                    | 0.7        | 0.8        | 6.8   | 8.6   | 0.010                |
| 1005RVV0020025  | 2 × 2.5                    | 0.8        | 0.9        | 8.2   | 10.3  | 0.012                |
| 1005RVV0030005  | 3 × 0.5                    | 0.6        | 0.7        | 5.5   | 7     | 0.010                |
| 1005RVV00300075 | 3 × 0.75                   | 0.6        | 0.8        | 6     | 7.6   | 0.010                |
| 1005RVV003001   | 3 × 1.0                    | 0.6        | 0.8        | 6.3   | 8     | 0.011                |
| 1005RVV0030015  | 3 × 1.5                    | 0.7        | 0.9        | 7.4   | 9.4   | 0.010                |
| 1005RVV0030025  | 3 × 2.5                    | 0.8        | 1          | 9     | 11.2  | 0.010                |
| 1005RVV0040005  | 4 × 0.5                    | 0.6        | 0.8        | 6.2   | 7.9   | 0.009                |
| 1005RVV00400075 | 4 × 0.75                   | 0.6        | 0.8        | 6.6   | 8.3   | 0.007                |
| 1005RVV004001   | 4 × 1.0                    | 0.6        | 0.8        | 6.9   | 8.7   | 0.006                |
| 1005RVV0040015  | 4 × 1.5                    | 0.7        | 0.9        | 8.2   | 10.2  | 0.011                |
| 1005RVV0040025  | 4 × 2.5                    | 0.8        | 1.1        | 10.1  | 12.5  | 0.010                |
| 1005RVV0050005  | 5 × 0.5                    | 0.6        | 0.8        | 6.8   | 8.6   | 0.010                |
| 1005RVV00500075 | 5 × 0.75                   | 0.6        | 0.9        | 7.4   | 9.3   | 0.009                |
| 1005RVV005001   | 5 × 1.0                    | 0.6        | 0.9        | 7.8   | 9.8   | 0.007                |
| 1005RVV0050015  | 5 × 1.5                    | 0.7        | 1          | 9.1   | 11.4  | 0.006                |
| 1005RVV0050025  | 5 × 2.5                    | 0.8        | 1.1        | 11    | 13.7  | 0.011                |
| 1005RVV0050005  | 6 × 0.5                    | 0.6        | 0.9        | 7.6   | 9.6   | 0.010                |
| 1005RVV00500075 | 6 × 0.75                   | 0.6        | 0.9        | 8.1   | 10.1  | 0.010                |
| 1005RVV005001   | 6 × 1.0                    | 0.6        | 1          | 8.7   | 10.8  | 0.009                |
| 1005RVV0050015  | 6 × 1.5                    | 0.7        | 1.1        | 10.2  | 12.6  | 0.007                |
| 1005RVV0050025  | 6 × 2.5                    | 0.8        | 1.2        | 12.2  | 15.1  | 0.006                |
| 1005RVV0070005  | 7 × 0.5                    | 0.6        | 0.9        | 8.3   | 10.4  | 0.011                |